



Plastic Chain Series

- Product Overview








Slat Top Chains


Straight Running Chains

Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 
uni 820 831 Strength: 2000 N (899 lbf)	uni 821 Strength: 3000 N (674 lbf)	uni 821 PRR Strength: 3000 N (674 lbf)

Side Flexing Chains

Pitch 19.1 mm (0.75 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 
uni 440 Tab Strength: 1100 N (247 lbf) Min radius: 175.0 mm (6.89 in)	uni 879 Tab* Tab R Strength: 2250 N (506 lbf) Min radius: 400.0 mm (15.75 in)* 200.0 mm (7.87 in)	uni 879 Tab Safety Finger Strength: 2250 N (506 lbf) Min radius: 200.0 mm (7.87 in)	uni 879 Tab Safety Strength: 2250 N (506 lbf) Min radius: 200.0 mm (7.87 in)

Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 
uni 879 Tab R G4 Strength: 2250 N (506 lbf) Min radius: 200.0 mm (7.87 in)	uni 880 Strength: 2250 N (506 lbf) Min radius: 400.0 mm (15.75 in)	uni 880 Tab* Tab R Strength: 2250 N (506 lbf) Min radius: 400.0 mm (15.75 in)* 200.0 mm (7.87 in)	uni 880 Tab RT Strength: 2250 N (506 lbf) Min radius: 200.0 mm (7.87 in)


Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 	Pitch 38.1 mm (1.50 in) 
uni 880 Super Flex Strength: 2250 N (506 lbf) Min radius: 457.0 mm (17.99 in) 610.0 mm (24.02 in)	uni 882 Tab Strength: 4000 N (899 lbf) Min radius: 610.0 mm (24.02 in) 700.0 mm (27.56 in)	uni 882 Tab SC Strength: 4000 N (899 lbf) Min radius: 610 mm (24.02 in)	uni 882 Tab PRR Strength: 4000 N (899 lbf) Min radius: 610 mm (24.02 in)

Snap On Chains

Straight Running Chains

Pitch 12.7 mm (0.50 in)  	Pitch 19.1 mm (0.75 in)  	Pitch 19.1 mm (0.75 in)  
uni 843 SK Strength SS: 1500 N (340 lbf) Strength carbon: 2000 N (450 lbf)	uni 863 Tab Strength SS: 2700 N (600 lbf) Strength carbon: 5500 N (1200 lbf)	uni 963 Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf)


Side Flexing Chains

Pitch 12.7 mm (0.50 in)  	Pitch 19.1 mm (0.75 in)  	Pitch 19.1 mm (0.75 in)  	Pitch 19.1 mm (0.75 in)  
uni 1843 Strength SS: 1500 N (340 lbf) Strength carbon: 2000 N (450 lbf) Min radius: 254 mm (10.0 in)	uni 1873 Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min radius: 356 mm (14.02 in) 457 mm (17.99 in)	uni 1873 Grip G3 Grip G4 Grip G4L Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min radius: 356 mm (14.02 in)	uni 1873 Grip D Strength SS: 2000 N (450 lbf) Strength carbon: 4000 N (900 lbf) Min radius: 356 mm (14.02 in)

Pitch 19.1 mm (0.75 in)  
uni 3873 Stainless steel: 2000 N (450 lbf) Carbon steel: 4000 N (900 lbf) Min radius: 356 mm (14.02 in)

Case Chains

Straight Running Chains

Pitch 66.3 mm (2.61 in)	
 	
uni NH78 Strength: T1: 9000 N (2023 lbf) T2: 7000 N (1574 lbf) T3: 6000 N (1349 lbf) T4: 6000 N (1349 lbf) T5: 5000 N (1124 lbf)	

Side Flexing Chains

Pitch 50.8 mm (2.00 in)	Pitch 50.8 mm (2.00 in)	Pitch 63.5 mm (2.50 in)	Pitch 63.5 mm (2.50 in)
 	 	 	 
uni 3200 Strength: 3150 N (708 lbf)	uni 3200 Tab Strength: 2525 N (568 lbf) Min radius: 406.0 mm (16.00 in)	uni 2600 C Tab C Strength: 6000 N (1686 lbf) Min radius: 600.0 mm (23.62 in)	uni 2600 O Tab O Strength: 6000 N (1686 lbf) Min radius: 600.0 mm (23.62 in)

Pitch 63.5 mm (2.50 in)	Pitch 70.0 mm (2.76 in)	Pitch 82.5 mm (3.25 in)	Pitch 82.5 mm (3.25 in)
 	 	 	 
uni 2500 Strength: 7500 N (1686 lbf) Min radius: 600.0 mm (23.62 in)	uni 2700 Strength: 11000 N (2473 lbf) Min radius: 300.0 mm (11.81 in)	uni 1400 Tab Strength: 8000 N (1798 lbf) Min radius: 450 mm (17.72 in)	uni 2800 Tab Strength: 6000 N (1349 lbf) Min radius: 500.0 mm (19.69 in)

Multi Flex Chains

Side Flexing Chains



uni 1700

Strength: 4000 N (899 lbf)
Min radius: 150.0 mm (5.91 in)



uni 1701 | Tab | Tab R*

Strength: 4000 N (899 lbf)
Min radius: 150.0 mm (5.91 in)
125.0 mm (4.92 in)*



uni 1702

Strength: 4000 N (899 lbf)
Min radius: 150.0 mm (5.91 in)



uni 1702 M

Strength: 4000 N (899 lbf)
Min radius: 150.0 mm (5.91 in)



uni 1703

Strength: 4000 N (899 lbf)
Min radius: 150.0 mm (5.91 in)



uni 1704

Strength: 4000 N (899 lbf)
Min radius: 137.5 mm (5.41 in)



uni 1705

Strength: 3100 N (689 lbf)
Min radius: 136.0 mm (5.35 in)



uni 1706

Strength: 3100 N (689 lbf)
Min radius: 150.0 mm (5.91 in)